



# MMG300Q060B6N

600V 300A IGBT Module

RoHS Compliant

JULY 2010


PRELIMINARY

## FEATURES

- Ultra Low Loss
- High Ruggedness
- High Short Circuit Capability
- Positive Temperature Coefficient
- Integrated Gate Resistor

## APPLICATIONS

- Invector
- Converter
- Welder
- SMPS and UPS
- Induction Heating



## ABSOLUTE MAXIMUM RATINGS

$T_C=25^{\circ}\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
<b>IGBT</b>				
$V_{CES}$	Collector - Emitter Voltage		600	V
$V_{GES}$	Gate - Emitter Voltage		$\pm 20$	V
$I_C$	DC Collector Current	$T_C=25^{\circ}\text{C}$	360	A
		$T_C=60^{\circ}\text{C}$	300	A
$I_{Cpuls}$	Pulsed Collector Current	$T_C=25^{\circ}\text{C}, t_p=1\text{ms}$	720	A
		$T_C=60^{\circ}\text{C}, t_p=1\text{ms}$	600	A
$P_{tot}$	Power Dissipation Per IGBT		833	W
$T_J$	Junction Temperature Range		-40 to +150	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range		-40 to +125	$^{\circ}\text{C}$
$V_{isol}$	Insulation Test Voltage	AC, $t=1\text{min}$	3000	V
<b>Free-Wheeling Diode</b>				
$V_{RRM}$	Repetitive Reverse Voltage		600	V
$I_{F(AV)}$	Average Forward Current	$T_C=25^{\circ}\text{C}$	300	A
		$T_C=60^{\circ}\text{C}$	250	A
$I_{F(RMS)}$	RMS Forward Current		440	A
$I_{FSM}$	Non-Repetitive Surge Forward Current	$T_J=45^{\circ}\text{C}, t=10\text{ms}, \text{Sine}$	1000	A
		$T_J=45^{\circ}\text{C}, t=8.3\text{ms}, \text{Sine}$	1090	A

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R .of China

Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: [www.macmicst.com](http://www.macmicst.com)

# MMG300Q060B6N

## ELECTRICAL CHARACTERISTICS

T<sub>C</sub>=25°C unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
<b>IGBT</b>						
V <sub>GE(th)</sub>	Gate - Emitter Threshold Voltage	V <sub>CE</sub> =V <sub>GE</sub> , I <sub>C</sub> =6mA	4.5	5.5	6.5	V
V <sub>CE(sat)</sub>	Collector - Emitter Saturation Voltage	I <sub>C</sub> =300A, V <sub>GE</sub> =15V, T <sub>J</sub> =25°C		1.95	2.45	V
		I <sub>C</sub> =300A, V <sub>GE</sub> =15V, T <sub>J</sub> =125°C		2.2		V
I <sub>CES</sub>	Collector Leakage Current	V <sub>CE</sub> =600V, V <sub>GE</sub> =0V, T <sub>J</sub> =25°C			1	mA
		V <sub>CE</sub> =600V, V <sub>GE</sub> =0V, T <sub>J</sub> =125°C		2		mA
I <sub>GES</sub>	Gate Leakage Current	V <sub>CE</sub> =0V, V <sub>GE</sub> =±20V	-0.8		0.8	μA
R <sub>Gint</sub>	Integrated Gate Resistor			2.5	3.5	Ω
Q <sub>ge</sub>	Gate Charge	V <sub>CC</sub> =300V, I <sub>C</sub> =300A, V <sub>GE</sub> =±15V		1480		nC
C <sub>ies</sub>	Input Capacitance	V <sub>CE</sub> =25V, V <sub>GE</sub> =0V, f=1MHz		13		nF
C <sub>oes</sub>	Output Capacitance			1.4		nF
C <sub>res</sub>	Reverse Transfer Capacitance			1.2		nF
t <sub>d(on)</sub>	Turn - on Delay Time	V <sub>CC</sub> =300V, I <sub>C</sub> =300A		125		ns
t <sub>r</sub>	Rise Time	R <sub>G</sub> =3 Ω, V <sub>GE</sub> =±15V		65		ns
t <sub>d(off)</sub>	Turn - off Delay Time	T <sub>J</sub> =25°C		300		ns
t <sub>f</sub>	Fall Time	Inductive Load		40		ns
t <sub>d(on)</sub>	Turn - on Delay Time	V <sub>CC</sub> =300V, I <sub>C</sub> =300A		135		ns
t <sub>r</sub>	Rise Time	R <sub>G</sub> =3 Ω, V <sub>GE</sub> =±15V		70		ns
t <sub>d(off)</sub>	Turn - off Delay Time	T <sub>J</sub> =125°C		330		ns
t <sub>f</sub>	Fall Time	Inductive Load		45		ns
E <sub>on</sub>	Turn - on Switching Energy	V <sub>CC</sub> =300V, I <sub>C</sub> =300A, T <sub>J</sub> =25°C		4		mJ
		R <sub>G</sub> =3 Ω, T <sub>J</sub> =125°C		6		mJ
E <sub>off</sub>	Turn - off Switching Energy	V <sub>GE</sub> =±15V, T <sub>J</sub> =25°C		6		mJ
		Inductive Load, T <sub>J</sub> =125°C		10		mJ
<b>Free-Wheeling Diode</b>						
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> =300A, V <sub>GE</sub> =0V, T <sub>J</sub> =25°C		1.25	1.6	V
		I <sub>F</sub> =300A, V <sub>GE</sub> =0V, T <sub>J</sub> =125°C		1.2		V
t <sub>rr</sub>	Reverse Recovery Time	I <sub>F</sub> =300A, V <sub>R</sub> =300V		240		ns
I <sub>RRM</sub>	Max. Reverse Recovery Current	di <sub>F</sub> /dt=-2000A/μs		170		A
Q <sub>rr</sub>	Reverse Recovery Charge	T <sub>J</sub> =125°C		24		μC

## THERMAL AND MECHANICAL CHARACTERISTICS

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
R <sub>thJC</sub>	Junction-to-Case Thermal Resistance	Per IGBT			0.15	K/W
R <sub>thJCD</sub>	Junction-to-Case Thermal Resistance	Per Inverse Diode			0.30	K/W
Torque	Module-to-Sink	Recommended (M6)	3		5	N·m
Torque	Module Electrodes	Recommended (M6)	2.5		5	N·m
Weight				200		g




Figure1. Typical Output characteristics




Figure2. Typical Transfer characteristics




Figure3. Switching Energy vs. Collector Current




Figure4. Switching Energy vs. Gate Resistor




Figure5. Switching Times vs. Collector Current




Figure6. Switching Times vs. Gate Resistor




Figure7. Gate Charge characteristics




Figure8. Typical Capacitances vs.  $V_{CE}$




Figure9. Reverse Biased Safe Operating Area




Figure10. Short Circuit Safe Operating Area




Figure11. Rated Current vs.  $T_C$




Figure12. Diode Forward Characteristics




Figure13. Transient Thermal Impedance of IGBT




Figure14. Transient Thermal Impedance of Diode





Figure15. Circuit Diagram



Dimensions (mm)  
Figure16. Package Outline